

Depth Filtration
BECO® SELECT™ A Range



Depth Filter Sheets for Spirits and Fragrance Filtration

BECO SELECT A depth filter sheets from Eaton's Begerow Product Line are used for the demanding filtration of high quality spirits, such as cognac, armagnac, barrel-matured brandy, and whisky. Also in the filtration of spirits based on pomaceous fruit, pitted fruit, soft fruit, yeast, and grapes, juniper berries (Gin, Genever), grain (Aquavit) excellent filtration results are achieved. The product range is graded from coarse particle separation to fine filtration and enables accurate adaptation to the requirements of spirits and fragrance filtration.

The specific advantages of BECO SELECT A depth filter sheets:

- Low content of calcium, magnesium and iron ions to avoid secondary hazes
- Color-preserving filtration through minimum color adsorption in the depth filter sheet
- Selective separation of long-chain fatty acid esters
- Reliable retention of the components to be separated through ideal pore structure
- High clarification effect through the use of high-quality raw materials
- Economic service life through high dirt holding capacity
- Comprehensive quality assurance for all raw and auxiliary materials and intense in-process controls ensure consistent quality of the finished products



Water throughput BECO SELECT A range



Conditions: Δ p = 14.5 psi (100 kPa, 1 bar), Medium: Water at 68 °F (20 °C)

Fine Filtration of Very Fine Haze Substances

BECO SELECT A 20

BECO depth filter sheets for achieving a high clarifying level. This depth filter sheet type reliably retains very fine particles and higher fatty acids. This makes them particularly suitable for haze-free storage and filling.

Clarification Filtration

BECO SELECT A 40

BECO depth filter sheets for clarification filtration and for the separation of medium-strong haze. This depth filter sheet type has a high dirt holding capacity and is particularly suitable for the filtration of spirits with a high fusel oil content.

Physical Data

This information is intended as a guideline for the selection of BECO depth filter sheets.

Type	Article no.	Nominal retention rate μm	Thickness in (mm)	Ash content %	Bursting strength wet		Water throughput at	
					psi	(kPa)	$\Delta p = 14.5 \text{ psi}$ gpm/ft ²	($\Delta p = 100 \text{ kPa}^*$ l/m ² /min)
SELECT A 20	27620	0.8	0.17 (4.4)	43.0	> 5.8	(40)	3.9	(160)
SELECT A 40	27640	2.5	0.17 (4.4)	43.0	> 5.8	(40)	7.4	(300)

The water throughput is a laboratory value characterizing the different BECO depth filter sheets. It is not the recommended flow rate.

* 100 kPa = 1 bar

The figures indicated are based on the current standard of knowledge. Subject to modification in the interest of further development of BECO depth filter sheets to improve quality. A manufacturer's certificate according to DIN EN 10204 can be issued on request.

Components

BECO depth filter sheets are made from particularly pure natural materials and cationic charge carriers. Different quantities of finely fibrillated cellulose fibers obtained from deciduous and coniferous trees, diatomaceous earth, and perlite are used.

Instructions for Correct Use

BECO depth filter sheets require careful handling when inserting them into the plate and frame filter. Avoid banging, bending, and rubbing the sheets. Do not use damaged depth filter sheets.

Inserting

Each BECO depth filter sheet has a rough side and a smooth side. The rough side of the depth filter sheet is the unfiltrate side; the smooth side is the filtrate side. Always ensure that the filtrate side is in contact with the clear filtrate plate when inserting the sheets.

Sanitizing and Sterilizing (Optional)

The wetted BECO SELECT A depth filter sheets may be sterilized with hot water or saturated steam up to a maximum temperature of **250 °F (121 °C)**. The pressed filter package should be loosened slightly. Make sure to sterilize the entire filter system thoroughly. Do not apply final pressure until after the filter package has cooled down.

Sterilizing with Hot Water

The flow velocity should at least equal the filtration capacity.

The water should be softened and free of impurities.

Temperature: > 185 °F (85 °C)

Duration: 25 minutes after the temperature has reached 185 °F (85 °C) at all valves.

Pressure: At least 7.2 psi (50 kPa, 0.5 bar) at the filter outlet.

Sterilizing with Steam

Steam quality: The steam must be free of foreign particles and impurities.

Temperature: Max. **250 °F (121 °C)**
(saturated steam)

Duration: Approx. 20 minutes after steam escapes from all filter valves.

Rinsing: After sterilizing with 13.2 gal/sqm (50 l/m²) at 1.25 times the flow rate.

Filter Preparation and Filtration

Unless already completed after sterilization, Eaton recommends pre-rinsing the closed filter with 13.2 gal (50 l) of water per square meter at 1.25 times the flow rate prior to the first filtration. Depending on the application, this usually equals a rinsing time of 10 to 20 minutes. Test the entire filter for leakage at maximum operating pressure.

High-proof alcohol solutions and chemical products that do not allow pre-rinsing with water, should be circulated for 10 to 20 minutes. Dispose of the rinsing solution after rinsing.

Safety

When used and handled correctly, there are no known unfavorable effects associated with this product.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

Waste Disposal

Due to their composition BECO depth filter sheets are biodegradable. Relevant current regulations must be followed, depending on the filtered product.

Storage

BECO depth filter sheets consist of strongly adsorbing materials. The product must be handled carefully during shipping and storage. Store the depth filter sheets in a dry, odor-free, and well ventilated place.

Do not expose the depth filter sheets to direct sunlight.

BECO depth filter sheets are intended for immediate use and should be used within 24 months of delivery.

Available Formats

All common square or round filter sizes are available for delivery. Special formats are available on request.

HS Customs Tariff: 4812 00 00

Quality Assurance According to DIN EN ISO 9001

Eaton's Begerow Product Line comprehensive Quality Management System has been certified according to DIN EN ISO 9001.

This certification verifies that a fully functioning comprehensive Quality Assurance System covering product development, contract controls, choice of suppliers, receiving inspections, production, final inspection, inventory management, and shipment has been implemented. Extensive quality assurance measures incorporate adherence to technical function criteria and chemical purity and quality recognized as safe under the German legislation governing the production of foods and beverages.

North America - HQ

44 Apple Street,
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America Only)
Voice: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Voice: +49 2486 809-0

Internormen Product Line

Friedensstraße 41
68804 Altlussheim, Germany
Voice: +49 6205 2094-0

Begerow Product Line

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Voice: +49 6704 204-0

Brazil

Av. Julia Gaioli, 474 - Bonsucesso
07251-500 - Guarulhos
Brazil
Voice: +55 11 2465 8822

China

No. 7 Lane 280 Linhong Road,
Changning District,
Shanghai 200335, China
Voice: +86 21 5200 0422

Singapore

4 Loyang Lane #04-01/02
Singapore 508914
Voice: +65 6825 1668

For more information, please e-mail us at filtration@eaton.com or visit us online at eaton.com/filtration for a complete list of Eaton's filtration products.

Not all products in Eaton's Begerow Product Line are available in all regions. Please contact your local Eaton office to determine availability.

© 2012 Eaton Corporation. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.