



SciLog SciCon® Sensors

- sensor technology
- pre-calibrated single-use or extended use

The only pre-calibrated, single-use conductivity sensors with a gamma-stable memory device that stores data of all calibration, and sensor specific information.

The SciLog SciCon® combines temperature sensing capabilities with conductivity sensing capabilities in a compact, disposable, single-use package at a low price point. Each sensor is pre-programmed and barcoded with a unique ID for easy traceability and data documentation when combined with the SciLog SciDoc software. Factory calibration data is also stored on each sensor's chip for out-of-box, plug and play use. The SciCon® comes in 5 different sizes to fit a variety of tubing sizes: Luer, $\frac{3}{8}$ " barb, $\frac{1}{2}$ " barb, $\frac{3}{4}$ " Tri-Clover and 1" Tri-Clover Ladish.

Features and Benefits

- Pre-calibrated
- NIST-traceable
- Certified calibration
- Extended-use sensors (optional)
- Gamma-stable
- NaOH stable
- Autoclave stable
- Comprehensive customer support



Note: SciCon® is a registered trademark of Parker Hannifin Corporation.

The SciCon® fully integrates and optimizes most existing systems involving...

- Aseptic filtration
- Chromatography
- Reverse osmosis
- Ultrapure water
- Bags and manifolds

SciCon® Range & Accuracy

- High range: 10 - 200 mS range (± 0.25 mS Accuracy)
- Low range: 0 - 100 μ S range (± 3 μ S Accuracy)



Sensor Specifications

Sterilizability

- Can be sanitized IPA 70%
NaOH (0.1N - 1.0N)
- Autoclavable: (1x)
- Gamma stable: 25-45 kGy

Material, Fluid Contact

- Medical grade polysulfone
- Meets USP Class VI and FDA 21CFR177.1520
- All wetted materials are made of animal-free compounds

Sensor Type

- 4-Electrode conductivity cell

Temperature Probe

- Thermistor

Sensor Microchip

- EPROM
- Stored sensor ID and calibration factor

Sensor Connector and Cables

- Dust and water proof IP67



SciCon® Family



Luer


 $\frac{3}{8}$ " Barb

 $\frac{1}{2}$ " Barb

 $\frac{3}{4}$ " Tri-Clover


1" Tri-Clover 'Ladish'

Size, Part Codes and Specifications

Connector Type	Part Code (Packs of 5)	Compatible Tubing Sizes	Max. Flow Rate*	Max. Pressure
Luer	080-599PSX-5	ID 0.03" to 0.31"	1 L / min	60 psi
$\frac{3}{8}$ " Barb	080-594PSX-5	IS 0.31" to 0.38"	8 L / min	60 psi
$\frac{1}{2}$ " Barb	080-595PSX-5	ID 0.50"	17 L / min	60 psi
$\frac{3}{4}$ " Tri-Clover (TC)	080-596PSX-5	Tubing with $\frac{3}{4}$ " TC	31 L / min	60 psi
1" Tri-Clover 'Ladish'	080-597PSX-5	Tubing with 1" TC Ladish	60 L / min	60 psi

Monitor Specifications

Sensitivity Range

- 1 μ S/cm to 200 mS/cm
- 0.1 μ S/cm resolution

Operating Mode / Auto Range Display

- Conductivity: 1 μ S/cm to 200 mS/cm
- Temperature: 0°C to 50°C

Analog Outputs

- 4-20 mA outputs
- 18 bit resolution

Digital Output

- RS-232

Alarm Outputs

- 4 TTL switches
- User-selectable hi/lo conductivity
- User-selectable hi/lo temperature

Power Supply

- 115/230 VAC



Description	Part Code
SciCon® Sensor Monitor	080-590
Sensor Cable (Sensor to Monitor) - 6 ft	090-0491
Sensor Cable (Sensor to Monitor)- 12 ft	090-0491-12