

## CAC

### CHEMAIR AIRLINE

Premium lightweight flexible airline hose. The added benefit of a chemical resistant tube makes it suitable for low pressure agriculture spray applications. Conforms to AS/NZS 2554 class B requirements.



# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
CAC-006-***	6	12	250	60	20 100 300#
CAC-008-***	8	14	250	70	20 100 300#
CAC-010-***	10	17	290	85	20 30 100 200#
CAC-012-***	12.5	19	250	95	20 100 200#
CAC-020-***	20	27.5	250	190	20 100

#### Common Applications:

- Rattle Guns
- Nail Guns
- Pneumatic Tools
- Ag Spray



## HAL

### BLUE ADFLEX AIRLINE

Flexible lightweight airline hose. It provides an economical alternative for users who do not require the higher working pressure of 10mm Chemair. Conforms to AS/NZS 2554 class B requirements.



# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
HAL-010-***	10	16	250	85	20 100 300#

#### Common Applications:

- Pneumatic Tools
- Portable Equipment



**Note:** Merchandiser reel available as a display unit, fitted with 1/4" BSP ends, using Part No. HAL-MR-010/20F

## BSW

### BLUE STRIPE WASHDOWN

Premium washdown hose designed specifically for cold washdown applications. Its distinctive white cover with blue stripe is smooth for ease of handling and its virgin PVC construction ensures unmatched performance, flexibility and service life.



# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
BSW-020-***	20	28	145	140	20 50 100
BSW-025-***	25	33	145	180	20 50 100
BSW-032-***	32	42	145	210	20 40 100
BSW-038-***	38	50	145	210	20 40 100

#### Common Applications:

- Golf Courses
- Bowling Greens
- Dairy's
- Parks and Gardens



# FOOD & MULTIPURPOSE/PETROLEUM

## NTP

### PETROL RESISTANT/FOOD CONTACT

Translucent dual purpose food contact/petrol hose with a distinctive red/gold tracer to identify its dual application. Conforms to AS/NZS 2070 for food contact requirements. Safety factor 4:1



#### Common Applications:

- Air Lines
- Water Transfer
- Transfer Line in Food Processing
- Petroleum Products
- Siphon Lines

# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
NTP-006-***	6	12	250	65	20 100 300#
NTP-008-***	8	14	250	75	20 100 300#
NTP-010-***	10	16	250	85	20 100 200#
NTP-012-***	12.5	19	250	100	20 100 200#
NTP-016-***	16	22	250	130	20 100
NTP-020-***	20	27.5	250	150	20 50 100
NTP-025-***	25	33	250	180	20 50 100
NTP-032-***	32	42	145	220	10 20 40
NTP-038-***	38	49	145	250	10 20 40
NTP-050-***	50	63	145	320	10 20 40



## HDW

### DRINKING WATER

Specifically formulated hose with EVA tube, designed to prevent the "flavouring" of drinking water. Conforms to AS/NZS 2070 for food contact requirements.



#### Common Applications:

- Potable Water in Caravans, Boats
- Transfer into drinking containers

# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
HDW-012-***	12	17.2	145	100	20 100 200#



## CMX CELLARMAX

For non-toxic applications requiring a heavy duty hose. Suitable for wine and fruit juice. Conforms to AS/NZS 2070 standards. Winery/food contact clear with red helix.



# Part Number	ID (mm)	OD (mm)	Ug Vacuum Rating (mmHg)	BR (mm)	Coil Length (metres)
CMX-025-***	25.5	33.1	735	70	20
CMX-032-***	32.2	40.2	735	110	20
CMX-038-***	38.5	46.9	735	150	20
CMX-050-***	51.2	60.2	735	200	20
CMX-063-***	64.4	75.2	720	290	20
CMX-075-***	76.2	87.4	720	350	20
CMX-100-***	102.2	115.0	675	570	20
CMX-125-***	127.8	141.8	675	760	20

### Common Applications:

- Wine transfer
- Food Processing
- Beverage Lines



## MFX MILKFLEX

For non-toxic applications. Suitable for use as a milk tanker suction and delivery hose. Conforms to AS/NZS 2070 standards. Food contact clear with white helix.



# Part Number	ID (mm)	OD (mm)	Ug Vacuum Rating (mmHg)	BR (mm)	Coil Length (metres)
MFX-025-***	25.5	31.9	515	75	20
MFX-032-***	32.2	39.2	515	110	20
MFX-038-***	38.5	46.5	515	150	20
MFX-050-***	51.2	60.2	515	210	20
MFX-063-***	64.4	74.4	515	290	20
MFX-075-***	76.2	86.6	515	350	20

### Common Applications:

- Milk Tankers
- Food Manufacturing



# STEAM & HOT WATER

## 7079

### ECW™ ECONOMY WHITE WASHDOWN

Primarily designed for use in food plants, breweries and any place a flexible, lightweight washdown hose is needed.



# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
707950250-GAA	12.7	23.0	250	70	137.0
707975250-GAA	19.1	32.0	250	125	122.0
707910250-GAA	25	39.0	250	150	92.0

**Tube:**

White EPDM

**Cover:**

White EPDM

**Reinforcement:**

Synthetic ply

**Temperature range:**

-40°C to +100°C

## 9583

### HOT WASHDOWN

Designed for floor and equipment washdown in dairies, creameries, food processing plants and paper mills.



# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
9583-012-***	13	23.0	116	100	20 60
9583-020-***	19	32.0	116	160	20 60
9583-025-***	25	39.0	116	200	20 60

**Tube:**

White heat resistant SBR

**Cover:**

White heat resistant SBR

**Reinforcement:**

Synthetic ply

**Temperature range:**

-40°C to +100°C

## 9582

### STANDARD STEAM

General purpose hose designed for use with saturated steam.



# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
9582-012-***	13	24.0	116	100	20 60
9582-020-***	19	32.0	116	160	20 60
9582-025-***	25	35.0	116	200	20 60
9582-032-***	32	46.0	116	250	20 60 [C]
9582-038-***	38	53.0	116	300	20 60
9582-050-***	51	67.0	116	400	20 60

**Tube:**

Black EPDM

**Cover:**

White EPDM

**Reinforcement:**

Synthetic ply

**Temperature range:**

-40°C to +170°C

# FOOD & BEVERAGE

## SW630

### TITANFLEX FOOD SUCTION/DELIVERY HOSE

Suction and delivery hose designed to handle non-fatty and non-oily foods, liquids, sanitary products and potable water in a variety of transfer applications. The lightweight construction incorporates a dual wire helix that provides full suction capabilities and kink resistance. Resistant to abrasion, mild chemicals and ozone.



# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
SW630-1500	38.1	54.0	200	114.3	30.48 [C]
SW630-2000	50.8	67.1	200	152.4	30.48 [C]
SW630-2500	63.5	80.2	200	190.5	30.48 [C]
SW630-3000	76.2	94.1	200	228.6	30.48 [C]
SW630-4000	101.6	120.3	200	304.8	30.48 [C]

**Tube:**

White Chlorobutyl

**Cover:**

Grey EPDM; wrapped finish

**Reinforcement:**

Textile Plies with dual wire helix

**Temperature Range:**

-40°C to +107°C

## SS200

### BREWERS DELIVERY HOSE

Delivery hose designed to handle beer, wine, non-fatty and non-oily foods, liquids and potable water in brewery and wine transfer applications. The EPDM cover is resistant to abrasion, mild chemicals and ozone.



# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
SS200-1500	38.1	60.3	350	152.4	30.48 [C]
SS200-2000	50.8	76.2	350	177.8	30.48 [C]
SS200-2500	63.5	88.9	350	203.2	30.48 [C]
SS200-3000	76.2	104.8	350	228.6	30.48 [C]
SS200-4000	101.6	130.2	350	304.8	30.48 [C]

**Tube:**

White Chlorobutyl

**Cover:**

Orange EPDM; wrapped finish

**Reinforcement:**

Multiple textile plies

**Temperature Range:**

-40°C to +82°C

## SP330

### LIGHT-N-BRIGHT FOOD SUCTION HOSE

Suction and delivery hose designed to handle non-fatty and non-oily foods, liquids, sanitary products and potable water in a variety of transfer applications. Series SP330 features a lightweight construction with an external PVC rod helix for full suction capability, superior flexibility and resistance to abrasion crushing and kinking.



# Part Number	ID (mm)	OD (mm)	WP (PSI)	BR (mm)	Coil Length (metres)
SP330-2000	50.8	76.2	100	50.8	30.48 [C]
SP330-2500	63.5	88.9	100	76.2	30.48 [C]
SP330-3000	76.2	101.6	100	101.6	30.48 [C]
SP330-4000	101.6	127.0	100	152.4	30.48 [C]

**Tube:**

White Chlorobutyl

**Cover:**

Red synthetic rubber with external gray PVC helix

**Reinforcement:**

Multiple textile plies (with dual wire helix 3" and 4" only)

**Temperature Range:**

-40°C to +93°C

**THREADED COUPLINGS & ADAPTORS**

Size mm	Hose ID	BRASS		POLYPROPYLENE		NR
		Female Nut & Tail	Male Lump End	Female Nut & Tail	Male Lump End	Replacement Washer
12	12	BRN-012	BRL-012	PPN-012	PPL-012	TNW-012
20	12	BRN-017	BRL-017			TNW-020
20	20	BRN-020	BRL-020	PPN-020	PPL-020	
25	12	BRN-022	BRL-022			TNW-025
25	20	BRN-023	BRL-023	PPN-023	PPL-023	
25	25	BRN-025	BRL-025	PPN-025	PPL-025	
32	25	BRN-027	BRL-027			TNW-032
32	32	BRN-032	BRL-032	PPN-032	PPL-032	
38	32	BRN-037	BRL-037			TNW-038
38	38	BRN-038	BRL-038	PPN-038	PPL-038	
50	38	BRN-047	BRL-047			TNW-050
50	50	BRN-050	BRL-050	PPN-050	PPL-050	
63	63	BRN-063	BRL-063			TNW-063
75	75	BRN-075	BRL-075	PPN-075	PPL-075	TNW-075
100	100	BRN-100	BRL-100			TNW-100

**HOSE NIPPLES/JOINERS & STEAM/HIGH PRESSURE FITTINGS**

Size mm	Nipples	Joiners	Male Stems	Ground Joints	Menders
12	CBP-012	HJP-012	MS-012	GJ-012	HPM-012
20	CBP-020	HJP-020	MS-020	GJ-020	HPM-020
25	CBP-025	HJP-025	MS-025	GJ-025	HPM-025
32	CBP-032	HJP-032	MS-032	GJ-032	HPM-032
38	CBP-038	HJP-038	MS-038	GJ-038	HPM-038
50	CBP-050	HJP-050	MS-050	GJ-050	HPM-050
63	CBP-063	HJP-063	MS-063	GJ-063	HPM-063
75	CBP-075	HJP-075	MS-075	GJ-075	HPM-075
100	CBP-100	HJP-100	MS-100	GJ-100	HPM-100
125	CBP-125				
150	CBP-150	HJP-150			
200	CBP-200	HJP-200			

**DRAGON BREATH STEAM COUPLINGS**

Female		Hose ID mm	Threaded Female mm
Wing Nut	Grip Nut		
7610-8BWGJF	7613-8BWGJF	12.7	25.4 NPSM
7610-12CSGJF	7613-12BWGJF	19.1	38.1 NPSM
7610-16CSGJF	7613-16BWGJF	25.4	38.1 NPSM

**Note:** For use with 7288 & 7264 Steam Hose

# CLAMPS

For low pressure clamping applications, Parkers wormdrive and superclamp products include a wide range of sizes and band widths with options for both stainless steel and zinc plated material grades.

(NON-SLOTTED)

## WORMDRIVE CLAMPS

Clamping Range mm	9mm Stainless Steel Band/Zinc Bolt		9mm Stainless Steel Band/Stainless Bolt		13mm Stainless Steel Band/Zinc Bolt		13mm Stainless Steel Band/Stainless Bolt	
	Pack of 10	Loose	Pack of 10	Loose	Pack of 10	Loose	Pack of 10	Loose
8-12		W2L-012						
8-16	W2L-016/10S	W2L-016	W4L-016/10S	W4L-016				
12-22	W2L-022/10S	W2L-022	W4L-022/10S	W4L-022				
16-25		W2L-025						
16-27	W2L-027/10S		W4L-027/10S	W4L-027				
20-32		W2L-032		W4L-032	W1S-032/10S	W1S-032	W4S-032/10S	W4S-032
25-40		W2L-040		W4L-040	W1S-040/10S	W1S-040	W4S-040/10S	W4S-040
30-45		W2L-045		W4L-045				
32-50		W2L-050		W4L-050	W1S-050/10S	W1S-050	W4S-050/10S	W4S-050
40-60		W2L-060		W4L-060	W1S-060/10S	W1S-060	W4S-060/10S	W4S-060
50-70		W2L-070		W4L-070	W1S-070/10S	W1S-070	W4S-070/10S	W4S-070
60-80						W1S-080		W4S-080
70-90					W1S-090/10S	W1S-090	W4S-090/10S	W4S-090
90-110					W1S-110/10S		W4S-110/10S	
110-130					W1S-130/10S		W4S-130/10S	
130-150					W1S-150/10S		W4S-150/10S	
140-160					W1S-160/10S		W4S-160/10S	

## EAR CLAMPS

Clamping Range mm	Part Number
5-7	EC2-070
7-9	EC2-090
9-11	EC2-110
11-13	EC2-130
13-15	EC2-150
14-17	EC2-170
15-18	EC2-180
17-20	EC2-200
20-23	EC2-230
22-25	EC2-250
23-27	EC2-270
25-28	EC2-280
28-31	EC2-310
34-37	EC2-370

