

Pure Fermentation SIHA® WhiteArome



Aroma Yeast, *Saccharomyces Cerevisiae*

SIHA WhiteArome from Eaton's Begerow Product Line is a newly selected pure yeast with special flavour formation for grape varieties such as Riesling, Pinot Blanc, Pinot Gris, Gutedel and Muscat.

The specific advantages of SIHA WhiteArome yeast:

- Reliable full fermentation at fermentation temperatures between 64 – 68 °F (18 – 20 °C)
- Harmonic white wines with good fruit aromatics
- Preservation of typical grape aromas
- Average yeast nutrient requirements

Application

As a basic rule, musts and mashes should be inoculated with SIHA WhiteArome yeast as early as possible. Longer maceration times promote uncontrolled propagation of wild yeast and undesired bacteria.

Application	Quantity required lb/1,000 gal (g/hl) under	
	normal fermentation conditions	difficult
White grape must	1.2 – 1.7 (15 – 20)	1.7 – 2.5 (20 – 30)
White grape mash	1.7 – 2 (20 – 25)	2 – 2.5 (25 – 30)

These quantities are guide values and should be adjusted to the individual conditions (healthiness of the grapes or fruit, yeast nutrients etc.)

The fermentation range is between 54 – 68 °F (17 – 25 °C). The optimum fermentation temperature is between 64 – 68 °F (18 – 20 °C).

SIHA WhiteArome yeast is best stirred into a 10:1 must/water mixture at 95 – 99 °F (35 – 37 °C), stirred again after approximately 2-3 hours and added to the must. Mixing is unnecessary if the must is pumped on to the yeast batch.

The addition of inactive yeast nutrients during rehydrogenation promotes the formation of active yeast cells and improves the fermentation performance of the yeast. We recommend a SIHA Proform Plus combined yeast nutrient dosage of 1.7 lb/1,000 gal (20 g/hl).

Product Characteristics

SIHA WhiteArome yeast is a selected yeast strain with pronounced grape-specific aroma formation (higher alcohols and their esters) in white wines.

The yeast strain is characterized by low formation of fermentation by-products such as SO₂, acetaldehyde, pyruvic acid and α-ketoglutarate. SIHA WhiteArome yeast suppresses undesired wild yeasts and bacteria through rapid start of fermentation and yeast cell multiplication.

The yeast can tolerate SO₂ quantities up to 2.28 gr/fl oz (50 mg/l).

SIHA WhiteArome yeast can produce up to 14% alcohol by volume. The practical alcohol yield is approximately 47% of the sugar content. For each lb (kg) of sugar fermented approx. 247 kJ(546 kJ)/59 kcal (130 kcal) of heat is released.

Safety

No safety specifications are required for SIHA WhiteArome yeast, as this product is used directly for food production. Storing, handling, and transporting this product do not create health or environmental hazards.

Storage

SIHA WhiteArome yeast is packed airtight in an aluminum sandwich film in an inert gas atmosphere. Since the product is vacuum-packed, it is easy to determine if the packaging is intact.

SIHA WhiteArome yeast can be stored at a temperature of 39 – 50 °F (4 – 10 °C) for a period of four years as long as the packaging is intact. The product can also be stored at 68 °F (20 °C) for short periods.

Opened packages should be used up immediately.

Delivery Information

SIHA WhiteArome yeast is sold under article no. 93.085 and is available in the following package sizes:

1.1.lb (500 g)	aluminum sandwich foil block pack
20 x 1.1.lb (500 g)	aluminum sandwich foil block pack in carton

HS Customs Tariff: 2102 10 90

Certified Quality

During the production process, SIHA WhiteArome yeast is constantly monitored to ensure consistently high quality. These inspections include wide-ranging technical functional criteria as well as safeness in accordance with relevant laws governing production of foods. Strict controls also take place immediately before and during final packaging.

SIHA WhiteArome yeast meets the purity criteria of the International Codex for Wine Processing Agents and complies with the German Wine Law.

North America - HQ

44 Apple Street,
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America Only)
Voice: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Voice: +49 2486 809-0

Internormen Product Line

Friedensstraße 41
68804 Altlusheim, Germany
Voice: +49 6205 2094-0

Begerow Product Line

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Voice: +49 6704 204-0

Brazil

Av. Julia Gaioli, 474 - Bonsucesso
07251-500 - Guarulhos
Brazil
Voice: +55 11 2465 8822

China

No. 7 Lane 280 Linhong Road,
Changning District,
Shanghai 200335, China
Voice: +86 21 5200 0422

Singapore

4 Loyang Lane #04-01/02
Singapore 508914
Voice: +65 6825 1668

For more information, please e-mail us at filtration@eaton.com or visit us online at eaton.com/filtration for a complete list of Eaton's filtration products.

Not all products in Eaton's Begerow Product Line are available in all regions. Please contact your local Eaton office to determine availability.

© 2013 Eaton Corporation. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.