

Enzyme Treatment SIHAZYM™ Claro

Granulated Wine Enzyme Compound for Must Pre-Clarification

SIHAZYM Claro enzyme from Eaton's Begerow Product Line is a pectolytic enzyme compound developed for fast and effective must pre-clarification. The high pectolytic activity based on polygalacturonase, pectinesterase, and pectinlyase promotes selective breakdown of pectins. High pectin content leads to poor mashing of grapes and poor must clarification.

In addition to traditional must pre-clarification/ sedimentation SIHAZYM Claro enzyme can also be used as a flotation enzyme.

The specific benefits of SIHAZYM Claro enzyme:

- Fast and effective must pre-clarification
- Higher quantity of free running must in grape varieties with high pectin content
- Reduction of juice viscosity

Application

SIHAZYM Claro enzyme is particularly suitable for a fast and effective depectinization of grape must. An alcohol test can be used to check the breakdown of pectin.

Based on the dosage recommendation the product is added directly into the must clarification tank as a 10% solution in water. Add SIHAZYM Claro enzyme to the enzyme solution in the reaction tank in order to ensure pectin breakdown before the actual flotation. For problematic mash from grapes with high pectin content, it is beneficial to add a combination of SIHAZYM Extro enzyme and SIHAZYM Claro enzyme into the press.

It is important to ensure optimum distribution of the enzyme solution in the must.

Activity

SIHAZYM Claro enzyme has an activity of 18,600 lb/dr (10,500 PGNU/g, polygalacturonase). The product is cleaned of cinnamyl esterase activity.

Dosage

Application	Dosage lb/1,000 gal (g/hl) must/mash	Duration
Sedimentation		
Must clarification (approx. 59 °F (15 °C))	0.08 – 0.17 (1 – 2)	2 – 4 h
Must clarification (approx. 46.4 – 50 °F (8 – 10 °C))	0.17 (2)	2 – 4 h
Red wine mash (flash pasteurization)	0.08 – 0.25 (1 – 3)	4 – 6 h
Must reserve preparation	0.17 – 0.25 (2 – 3)	6 – 12 h
Flotation	0.17 – 0.25 (2 – 3)	2 – 4 h

The optimum temperature is 68 °F (20 °C). For lower temperatures, higher SIHAZYM Claro enzyme dosages are required in order to ensure consistent activity.

Special Notes

Contact with bentonite causes irreversible damage to enzymes through adsorption.

The enzymatisation reaction must be completed prior to using bentonite, or the bentonite must be removed before the enzyme is added.

Any bentonite treatment that may be required should therefore be carried out before the enzyme treatment, because otherwise the enzyme would be adsorbed and deactivated by the bentonite. The application of up to 2.14 dr/gal (1,000 mg/l) SO₂ has no influence on enzyme activity.

Each packaging unit includes a dosing spoon:

0.22 lb (100 g) can – 0.01 lb (5 g) dosing spoon

1.1 lb (500 g) can – 0.02 lb (10 g) dosing spoon

Safety and Purity

The product is a white, virtually dust-free, and soluble micro-granulate without preservatives. It meets the requirements of the FAO/WHO JEFCA and FCC recommendations for food enzymes.

Further safety information can be found in the relevant Material Safety Data Sheet, which can be downloaded from our website.

Storage

SIHAZYM Claro enzyme is a micro-granulate that can be stored for up to three years at 39.2 – 42.8 °F (4 – 6 °C, ~ refrigerator temperature) without losing its designated activity.

The product should be stored dry and well-sealed once opened.

Delivery Information

SIHAZYM Claro enzyme is sold under article no. 95.229 and is available in the following package sizes:

0.22 lb (100 g) can

1.1 lb (500 g) can

HS Customs Tariff: 3507 90 90

Certified Quality

During the production process, SIHAZYM Claro enzyme is regularly monitored to ensure consistently high quality.

These inspections include technical functional criteria as well as safeness in accordance with relevant laws governing production of foods. Strict controls are additionally carried out immediately prior to and during final packaging.

North America - HQ

44 Apple Street,
Tinton Falls, NJ 07724
Toll Free: 800 656-3344
(North America Only)
Voice: +1 732 212-4700

Europe/Africa/Middle East

Auf der Heide 2
53947 Nettersheim, Germany
Voice: +49 2486 809-0

Internormen Product Line

Friedensstraße 41
68804 Altlusheim, Germany
Voice: +49 6205 2094-0

Begerow Product Line

An den Nahewiesen 24
55450 Langenlonsheim, Germany
Voice: +49 6704 204-0

Brazil

Av. Julia Gaioli, 474 - Bonsucesso
07251-500 - Guarulhos
Brazil
Voice: +55 11 2465 8822

China

No. 7 Lane 280 Linhong Road,
Changning District,
Shanghai 200335, China
Voice: +86 21 5200 0422

Singapore

4 Loyang Lane #04-01/02
Singapore 508914
Voice: +65 6825 1668

For more information, please e-mail us at filtration@eaton.com or visit us online at eaton.com/filtration for a complete list of Eaton's filtration products.

Not all products in Eaton's Begerow Product Line are available in all regions. Please contact your local Eaton office to determine availability.

© 2013 Eaton Corporation. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners.

All information and recommendations appearing in this brochure concerning the use of products described herein are based on tests believed to be reliable. However, it is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Eaton as to the effects of such use or the results to be obtained. Eaton assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations.



Powering Business Worldwide